

**Material Safety Data Sheet**  
**OSHA's Hazard Communication Standard**  
**U.S. Department of Labor**

29CFR1910

OMB No. 1218-0072

Identity No. 1207

Name: MBSilane Professional Marine Polish

**SECTION 1**

**Manufacturer Name :** MB International USA, Company  
**Address :** 7892 Sunflower Lane  
**City :** La Palma **State :** California  
  
**Date Prepared :** February 3, 2006

**Emergency No. :** 714-306-0414  
**Phone No. :** 626-815-4989  
**Contact Person :** Brian Tim Lee

**SECTION 2 – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

| <b>Hazardous Ingredients</b> | <b>CAS#</b> | <b>TLV(Units)</b> | <b>PEL</b> |
|------------------------------|-------------|-------------------|------------|
| None                         | None        | None              | None       |

**SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS**

|  |                              |                            |
|--|------------------------------|----------------------------|
| <b>Boiling Point :</b> (F) 212                                 | <b>Solubility :</b> Miscible | <b>pH :</b> NA             |
| <b>Percent Volatile :</b> ND                                   | <b>Vapor Density :</b> ND    | <b>Vapor Pressure :</b> NA |
| <b>Evaporation Rate(Butyl Acetate = 1) :</b> ND                |                              |                            |
| <b>Appearance &amp; Odor :</b> Thick Opaque Brown, Spice Odor. |                              |                            |

**SECTION 4 – FIRE AND EXPLOSION HAZARD INFORMATION**

**Flash Point :** > 200F  
**Flammable Limits :** N/A **Low :** N/A **Upper :** N/A  
**Fire/Explosion Hazards :** None  
**Extinguishing Media :** Foam, CO2, Dry Chemical  
**Fire Fighting Procedures :** Fire fighters should wear self-contained breathing apparatus and full protective clothing. Using water spray to cool nearby containers and structures exposed to fire.

**SECTION 5 – HEALTH HAZARD INFORMATION**

**Permissible Exposure Level :** ND  
**Eye :** Slight irritation  
**Skin :** Possible slight irritation  
**Inhalation :** None  
**Skin :** Possible slight irritation  
  
**Ingestion :** Ingesting large quantities may cause nausea.  
This material is not listed as a carcinogen by IARC, NTP or OSHA.  
**HMIS Hazard Class :** Health = 1 Flammability = 1 Reactivity = 0 Other = N/A  
Ranking : 0=Least 1=Slight 2=Moderate 3=High 4=Extreme

**FIRST AID**

**Eye Contact :** Flush with water for 15 minutes lifting eyelids. Get medical attention immediately.  
**Skin Contact :** Immediately flush skin with water for 15 minutes. Remove and launder contaminated clothing before use.  
**Inhalation :** Remove victim to fresh air. Administer artificial respiration if breathing ceases. Get medical attention immediately.  
**Ingestion :** Do not induce vomiting. Give lots of water, if conscious. Get medical attention immediately.

**SECTION 6 – REACTIVITY INFORMATION**

**Stability :** Stable  
**Reactivity :** None will occur.  
**Hazardous Decomposition Ingredients :** As with any organic material, CO and CO2 may be expected as by-products of combustion.  
**Hazardous Polymerization :** Will not occur.

**SECTION 7 – SPILL, LEAK AND DISPOSAL PROCEDURES**

**Small spills :** Absorbs with an inert material such as sand or vermiculite and sweep up and dispose of in accordance with Federal, State and local regulations.  
**Disposal :** Dispose of in accordance with Federal, State, and local regulations.

**NOTICE**

All information appearing herein is based on data obtained from chemical manufacturers and/or recognized technical sources. While the information is believed to be accurate, MB International USA, Company makes no representations as to its accuracy or sufficiency. Conditions of use are beyond MB International USA, Company's control and therefore users are responsible for and assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.